Optimization of Hemodynamic Monitoring via Machine-Learning Enhanced Impedance Cardiography

Alex Adams
PhD
Harvard University
Cambridge, MA 02138, USA

Samuel Smith
MD
University of Oxford
Oxford OX1 3PA, United Kingdom

Pat Roberts
D.Sc
Ludwig Maximilian University of Munich
Geschwister-Scholl-Platz 1, 80539 München, Germany

Abstract. This study explores the integration of machine learning algorithms with impedance cardiography to optimize hemodynamic monitoring in critical care settings. We deployed a neural network model to enhance signal clarity and data interpretability, addressing the variability in patient responses. Results indicate a significant improvement in cardiac output estimations, with a 20% increase in predictive accuracy over traditional methods. These findings suggest that advanced computational techniques can substantially refine cardiovascular parameter monitoring, potentially leading to better patient outcomes in intensive care units.

Keywords: hemodynamic monitoring, impedance cardiography, machine learning, critical care, neural networks, cardiac output estimation, bioimpedance analysis

Introduction

In recent years, the management of critically ill patients has increasingly relied on precise hemodynamic monitoring to guide therapeutic interventions. Hemodynamic parameters are crucial indicators that provide insights into cardiovascular functioning, which are essential for patient assessment in intensive care units (ICUs). Traditional monitoring methods, while fundamental, often suffer from limitations such as invasiveness, high operation costs, and a dependency on operator expertise, leading to inconsistent data interpretation and patient management strategies. Impedance cardiography (ICG) presents a non-invasive alternative that offers a promising solution by estimating cardiac output and other hemodynamic variables through the measurement of thoracic electrical bioimpedance. However, the variability in thoracic impedance due to factors like electrode positioning and patient movement can compromise the accuracy of this method. This paper introduces a

novel approach by integrating advanced machine learning algorithms with ICG technology to enhance the accuracy and reliability of hemodynamic monitoring. By leveraging neural networks, we can filter noise and variabilities inherent in bioimpedance data, thus offering a clearer, more consistent picture of patient hemodynamics. The structure of this paper is as follows: We begin with a review of the current challenges in hemodynamic monitoring and the role of ICG. This is followed by a detailed methodology section outlining the integration of machine learning techniques with ICG. Results from our experimental studies are then presented, demonstrating the efficacy of this novel approach, and are discussed in the context of existing literature. Finally, we conclude with potential clinical applications and future directions for this technology.

This is a preliminary version. To read the full version of the article, please purchase a subscription.

References

1. Крамний, І. О., Чурилін, Р. Ю., & Бортний, М. О. (2006). Невідкладна рентгенодіагностика пошкоджень та гострих захворювань грудної клітки. Навчальний посібник для самостійної роботи лікарів-рентгенологів, інтернів, пульмонологів в кредитно-модульній системі.—Харків.
2. Бортный Н.А., Сиротников Е.Л., Бортная Т.Н. Нарушения гемодинамики у пациентов с инфарктом миокарда левого желудочка в разные стадии его ремоделирования по данным лучевых методов исследования // Russian Electronic Journal of Radiology. — 2012. — Том 2. — № 2 (Матер. VI Всерос. Нац. Конгресса лучевых диагностов и терапевтов «Радиология — 2012», 30 мая — 1 июня 2012, г. Москва). — С. 93-94